





T A B L E

LED DRIVER CE - cULus Listed WITH INTERCHANGEABLE ELECTRICAL PLUGS FOR EU - UK - USA



	SMART VERSION	Premium VERSION
AIR FLOW	126 m ³ /h	126 m ³ /h
APP DEVICE	iOS & ANDROID	iOS & ANDROID
IOT 4.0	✓	✓
SMART CONTROL	CASAMBI 	CASAMBI 
TOUCH ON / OFF - SELECT MODE	✓	✓
FILTERS	PREFILTER (DUST CAPTURE) TiO ₂ FILTERS + UV-A LED	PREFILTER (DUST CAPTURE) TiO ₂ FILTERS + UV-A LED
NOISE	from 15 dBa to 50 dBa	from 15 dBa to 50 dBa
RATED VOLTAGE	110 ÷ 240 Vac	110 ÷ 240 Vac
POWER CONSUMPTION	38 W	38 W
ROOM COVERAGE	UP TO 80 m ² *	UP TO 80 m ² *
AIR QUALITY SENSOR	TEMPERATURE - HUMIDITY PRESSURE - TVOC CO2 rel. - IAQ - AIR FLOW	TEMPERATURE - HUMIDITY PRESSURE - TVOC CO2 rel. - IAQ - AIR FLOW INFLAMMABLE GAS - PM10

VERSION AVAILABLE AT THE END OF 2021

[*] The flow rate is indicative, as it varies according to the type of environment / ventilation present.
The data shown refers to an open space (ceiling 3m / h) and with forced ventilation (e.g. shops / offices)