



IZURA

- LED pendant luminaire with direct and indirect light
- Cover colour variants: black, white, bronze, gold, inox and selected patterns
- Developed according to the principles of circular design, with a basic structure with 3 interchangeable main elements: cover, housing, shades
- Easy installation and dismantling
- Colour variants of gear tray: black or white
- Colour variants of reflector brackets: black or white
- Cover: laser-cut sheet metal
- Luminaire available in 2 lengths
- Closed optical system with protective covers on LED modules to prevent damage from electrostatic discharge
- Glare control compliant to EN 12464-2011 with L65 < 3000 cd/m² and UGR < 16 for DSE workstations
- Colour temperature: 3500 K
- Colour rendering Ra > 90 for office applications
- With DALI-controllable converter or without converter
- LED service life: 100,000 h up to a luminous flux decrease to 95% of initial value
- Colour tolerance: initial MacAdam 2

An Environmental Product Declaration (EPD) is available for the following products.

IZU DI 10k-935 L12 LDE WH GWHD HWHD	70512613
IZU DI 12k5-935 L15 LDE BK GWHD HWHD	70512683
IZU D/I 10k-935 L12 LDE WH GWHD HWHD	70512803
IZU D/I 12k5-935 L15 LDE BK GBKD HBKD	70515347